

Claim Amendment under 37 CFR 1.121(c)

1. (Currently amended) A facial bone contouring device using a hollowed rasp provided with non-plugging holes
- 5 formed through a cutting plane, comprising:
- a rasp including a rod, and a cutter provided with a plurality of grooves for exhausting cut bone fragments, a saline solution feeding passage and a bone fragment exhausting passage formed in the cutter;
- 10 a powered surgical handpiece connected to the rasp for providing linear reciprocating motion to the rasp;
- a saline solution feeding unit for feeding saline solution to the saline solution feeding passage of the rasp; ~~and~~
- 15 a suction unit for sucking the cut bone fragments from the rasp via the bone fragment exhausting passage and then exhausting the cut bone fragments to the outside; and
- a protector, formed to have a cylindrical shape,
- 20 configured to accept and surround the entire surface of the rod and a part of the cutter of the rasp, wherein the protector is configured to be inserted with a trocar,
- wherein bone cutting is performed under the condition that the saline solution is fed into the rasp,
- 25 and the cut bone fragments are exhausted to the outside together with the saline solution, so that the bone cutting is continuously performed, and wherein the protector is configured to be separated from the rasp, to accept the trocar, to be delivered to a bone cutting site,
- 30 to release the trocar, and to accept the rasp in the original place such that the rasp is disposed at the bone cutting site via a minimum incision.

2. (Original) The facial bone contouring device using a hollowed rasp provided with non-plugging holes formed through a cutting plane, as set forth in claim 1, wherein a bone fragment collector is connected to the
5 suction unit.

3. (Currently amended) The facial bone contouring device using a hollowed rasp provided with non-plugging holes formed through a cutting plane, as set forth in
10 claim 1, wherein the rasp further includes+
a connector formed on one end of the rod having a cylindrical shape and connected to an adaptor of the powered surgical handpiece~~+~~, and
a-wherein the cutter, formed on the other end of the
15 rod, ~~having-comprises~~ a cutting blade formed at a lower portion of the cutter, a cavity formed in the cutter, and
~~a-wherein the~~ plurality of grooves connecting the cavity to the cutting blade~~+~~, and
wherein the saline solution feeding passage and the
20 bone fragment exhausting passage formed in the cutter are extended to the outside of the cutter.

4. (Original) The facial bone contouring device using a hollowed rasp provided with non-plugging holes
25 formed through a cutting plane, as set forth in claim 3, wherein the saline solution feeding passage and the bone fragment exhausting passage are formed in the rod.

5. (Original) The facial bone contouring device
30 using a hollowed rasp provided with non-plugging holes formed through a cutting plane, as set forth in claim 1, wherein the saline solution feeding passage is formed in the rod, and the bone fragment exhausting passage is formed by connecting the cavity in the cutter to an

external connection jack protruding from the cutter via a hole formed through the cutter.

6. (Canceled)

5

7. (Currently amended) The facial bone contouring device using a hollowed rasp provided with non-plugging holes formed through a cutting plane, as set forth in claim 1, wherein+ a bending portion is formed at a designated portion of the rod; and wherein a cylindrical protector, formed to have a cylindrical shape so as to surround the rod and a part of the cutter of the rasp, has a double tube structure so that the saline solution feeding passage is formed between two tubes, and is bent at a designated angle.

10

15